



L.T.F

Low Voltage Dimmable Wall Plug Power Supply

15W Dimmable Plug In with Optional Integrated Dimmer TA15WA/D12 & TA15WA/D24 Series



Efficiency	higher than 85%
Power Factor	>95%
Case TC	90°C Max.
Protection	Input/Output
Storage	-30°C/+90°C
Class	Class 2 Power Supply
Dimming	ELV Dimmable
Dimming Option	Integrated Dimmer



FEATURES

- Integrated dimming option available with on/off switch
- No load technology, works with both Halogen & LED AC loads
- Isolated output power per NEC and UL safety requirements
- UL listed, UL 8750, 1310
- Auto-reset ; Short circuit, Overload and Thermal protection
- Dimmable with ELV type dimmers
- Flicker free dimming and excellent dimming range
- 6' 18/2 SPT-1 attached power cord with 1/4' stripped lead wires
- Class 2 power supply
- Efficient, high power factor, low THD
- For dry location use only

ELECTRICAL SPECIFICATIONS

120V					
Model #	Input Voltage	Input Current	Output Current	Weight*	Available Form Factors
TA15WA12LEDPL1	120V AC 50/60Hz	0.12 A	12 AC	208.5g	PL1
TA15WA24LEDPL1	120V AC 50/60Hz	0.12 A	24 AC	208.5g	PL1
TA15WD12LEDPL1	120V AC 50/60Hz	0.12 A	12 DC	208.5g	PL1
TA15WD24LEDPL1	120V AC 50/60Hz	0.12 A	24 DC	208.5g	PL1

* Weight based upon weight of -PL1 model plug in without integrated dimmer.

L.T.F, L.L.C. PHONE: (847) 498-5832 FAX: (773) 337-5628 EMAIL: sales@ltftechnology.com
Company's Address: 2905 MacArthur Blvd Northbrook, IL 60062 U.S.A. www.ltftechnology.com

© L.T.F., L.L.C. All rights reserved. L.T.F. reserves the right to change specification for product improvements without notification



MECHANICAL SPECS.

Available Form Factors	Dimensions
PL1	90x49x33mm

Dimensions listed at widest part

