



L.T.F

Low Voltage Dimmable Wall Plug Power Supply

**30W Dimmable Plug In with Optional Integrated Dimmer
TA30WA/D12 & TA30WA/D24 Series**



| | |
|-----------------------|----------------------|
| Efficiency | higher than 85% |
| Power Factor | >95% |
| Case TC | 90°C Max. |
| Protection | Input/Output |
| Storage | -30°C/+90°C |
| Class | Class 2 Power Supply |
| Dimming | ELV Dimmable |
| Dimming Option | Integrated Dimmer |



RoHS



Year Warranty

FEATURES

- Integrated dimming option available with on/off switch
- No load technology, works with both Halogen & LED AC loads
- Isolated output power per NEC and UL safety requirements
- UL listed, UL 8750, 1310
- Auto-reset ; Short circuit, Overload and Thermal protection
- Dimmable with ELV type dimmers
- Flicker free dimming and excellent dimming range
- 6' 18/2 SPT-1 attached power cord with 1/4' stripped lead wires
- Class 2 power supply
- Efficient, high power factor, low THD
- For dry location use only

ELECTRICAL SPECIFICATIONS

| 120V | | | | | |
|----------------|-----------------|---------------|----------------|---------|------------------------|
| Model # | Input Voltage | Input Current | Output Current | Weight* | Available Form Factors |
| TA30WA12LEDPL1 | 120V AC 50/60Hz | 0.25 A | 12 AC | 208.5g | PL1 |
| TA30WA24LEDPL1 | 120V AC 50/60Hz | 0.25 A | 24 AC | 208.5g | PL1 |
| TA30WD12LEDPL1 | 120V AC 50/60Hz | 0.25 A | 12 DC | 208.5g | PL1 |
| TA30WD24LEDPL1 | 120V AC 50/60Hz | 0.25 A | 24 DC | 208.5g | PL1 |

* Weight based upon weight of -PL1 model plug in without integrated dimmer.

L.T.F, L.L.C. PHONE: (847) 498-5832 FAX: (773) 337-5628 EMAIL: sales@ltftechnology.com
Company's Address: 2905 MacArthur Blvd Northbrook, IL 60062 U.S.A. www.ltftechnology.com

© L.T.F., L.L.C. All rights reserved. L.T.F. reserves the right to change specification for product improvements without notification



MECHANICAL SPECS.

| Available Form Factors | Dimensions |
|------------------------|------------|
| PL1 | 90x49x33mm |

Dimensions listed at widest part

