



L.T.F.

Low Voltage Quick Connect Canopy

**60W and 75W Series
4CANRNDQJ-XXXX**



Efficiency	> 85%
Power Factor	98%
Case TC	90C° Max.
Protection	Input / Output
Storage	-30°C / +90°C
Humidity	95% RH Max.
Class	Class 2 Power Supply
Dimming	ELV Dimmable



RoHS



FCC Part 15
Class B Compliant

FEATURES

- Compatible with most of the premier low voltage Quick Jack and Free Jack connectors/fixtures in the United States market
- Dimmable with ELV type dimmers
- Low profile design with no visible mounting screws
- Available in multiple finishes
- Transformer options for both halogen and LED loads



*Ask for more information

ELECTRICAL SPECIFICATIONS

60W					
Model #	Input	Wattage	Output Voltage*	Finish	Load Type
4CANRNDQJ60LEDSN	120V AC, 0.5A 50/60Hz	60W	11.8V AC/DC	Satin Nickel	Halogen & AC LED bulbs
4CANRNDQJ60LEDCH				Chrome	
4CANRNDQJ60LEDBZ				Brown Bronze	
4CANRNDQJ60LEDBL				Black	
4CANRNDQJ60LEDWH				White	
4CANRNDQJ60LEDWH				Nickel	
4CANRNDQJ60LEDC				Custom	

*Also available in constant current configurations



ELECTRICAL SPECIFICATIONS

75W					
Model #	Input	Wattage	Output Voltage*	Finish	Load Type
4CANRNDQJ75SN	120V AC, 0.62A 50/60Hz	75W	11.8V AC/DC	Satin Nickel	Halogen Bulbs
4CANRNDQJ75CH				Chrome	
4CANRNDQJ75BZ				Brown Bronze	
4CANRNDQJ75BL				Black	
4CANRNDQJ75WH				White	
4CANRNDQJ75WH				Nickel	
4CANRNDQJ75C				Custom	

*Also available in constant current configurations

MECHANICAL SPECIFICATIONS

