



L.T.F.

Dimmable Low Voltage LED Driver - CLASS 2

60W DA60W-0000 Series 120V Plug-In LED Driver Constant Current and Constant Voltage



Efficiency	> 85%
Power Factor	> 0.9
Case TC	80°C Max.
Protection	Input / Output
Storage	-30°C / +80°C
Humidity	95% RH Max.
IP Rating	IP 44
Class	Class 2 Power Supply
Dimming	TRIAC, ELV



RoHS



FEATURES

- TRIAC and ELV dimmable
- Exceeds Title 24 requirements
- Isolated output power per NEC and UL safety requirements
- UL recognized / Listed, UL8750, UL1310
- Auto-reset; short circuit, overload and thermal protection
- Superior thermal performance
- Low profile, small form factor
- Efficient, high power factor, low THD, < 20%
- Constant current or constant voltage models
- Class 2 power supply and other than Class 2 options
- Custom colors available
- Includes 6' input cord (detachable, 3 prong connector) and 6' output cord (attached)

ELECTRICAL SPECIFICATIONS

Constant Current					
Model #	Input	Wattage	Output Voltage	Output Current	Form Factor
DA60W700C6786PL2-0000	120V AC 0.6A, 50/60Hz	60W	67-86V DC	700mA	PL2
DA60W780C5877PL2-0000			58-77V DC	780mA	
DA60W850C5070PL2-0000			50-70V DC	850mA	
DA60W950C4463PL2-0000			44-63V DC	950mA	
DA60W1050C3857PL2-0000			38-57V DC	1050mA	
DA60W1100C3655PL2-0000			36-55V DC	1100mA	
DA60W1200C3150PL2-0000			31-50V DC	1200mA	
DA60W1400C2443PL2-0000			24-43V DC	1400mA	
DA60W2000C1837PL2-0000			18-37V DC	1600mA	
DA60W2200C1433PL2-0000			14-33V DC	1800mA	
DA60W2400C1130PL2-0000			11-30V DC	2000mA	

LED Driver - DA Series - Class 2



L.T.F.

Dimmable Low Voltage LED Driver - CLASS 2

**60W DA60W-0000 120V Plug-In LED Driver Series
Constant Current and Constant Voltage**

ELECTRICAL SPECIFICATIONS

Constant Voltage					
Model #	Input	Wattage	Output Voltage	Load	Form Factor
DA60W12VPL2-0000	120V AC 0.6A, 50/60Hz	60W	12V DC	12V DC LED, 5A Max.	PL2
DA60W24VPL2-0000			24V DC	24V DC LED, 2.5A Max.	
DA60W36VPL2-0000			36V DC	36V DC LED, 1.67A Max.	
DA60W48VPL2-0000			48V DC	48V DC LED, 1.25A Max.	

MECHANICAL SPECS

Form Factor	Dimensions
"PL2"	134 x 63 x 38mm

PL2

