



**L.T.F.**

# Low Voltage Electronic Power Supply

**TA60WA24LED65B15**

**No-Load Electronic Transformer**



Efficiency	> 85%
Power Factor	> 98%
Case TC	90°C Max.
Protection	Input / Output
Storage	-30°C / +90°C
Humidity	95% RH Max.
IP Rating	IP 65
Class	Class 2 Power Supply
Dimming	ELV, Optional 0-10V



**RoHS**



FCC Part 15  
Class B Compliant



## FEATURES

- No load technology, works with both Halogen & LED AC loads.\*\*
- Isolated output power per NEC and UL safety requirements.
- UL recognized / listed Class 2 power supply, meets UL2108 requirements.
- FCC Part 15 Class B compliant.
- Soft start, auto-reset, short circuit, overload and thermal protection.
- Ingress protection IP65 rated.
- Dimmable with ELV type dimmers.
- Optional 0-10V dimming.
- Low profile, small compact design to fit in most enclosures.

## ELECTRICAL SPECIFICATIONS

Model #	Wattage	Input Voltage	Output Voltage	Load Type	Form Factor	Dimming
TA60WA24LED65B15	60W	120V AC, 0.5A 50/60Hz	24V AC	AC LED Bulbs, Incandescent & Halogen Bulbs	B7	ELV

## MECHANICAL SPECS

Available Form Factors	Dimensions
"B7"	2 <sup>25</sup> / <sub>32</sub> " x 1 <sup>19</sup> / <sub>32</sub> " x 2 <sup>9</sup> / <sub>32</sub> " 70.5 x 40 x 22.5mm

## B7

