



Optional Photo Control Installation Instructions

SAVE THESE INSTRUCTIONS

- A) Make sure power is off and transformer is NOT plugged into an electrical outlet.
NOTE: No splice is required, transformer is equipped with jumper connector.
- B) Open front cover of the transformer case by lifting the cover up. Locate and disconnect the white jumper connector inside the housing.
*Save the jumper connector with these instructions for possible future use.
- C) Remove one (1) of the 7/8" diameter knockouts on the side of the transformer and push the photo control white connector through the knockout hole. Inside the housing, slide the spacer and star nut over the white connector and thread it on to the photo control and tighten.
- D) Plug photo control white connector into the housing connector. Ensure that the side latch locks the connectors.
- E) Locate transformer and position photo control so that no lighting will shine on the cell. It will cause the photo control to cycle on and off.
*In the unlikely event that the photo control should fail, the lighting fixtures will remain on, even in the daytime. If this should happen, follow these instructions and remove the defective photo control and place the jumper connector in its place.
- F) Plug power supply into standard 115/120V receptacle. **NOTE:** The power supply cord must be plugged into a weather tight receptacle equipped with a Ground Fault Circuit Interrupter (GFCI).



This fixture is intended for installation in accordance with the National Electrical Code and local code specifications. Failure to adhere to these codes and instructions may result in serious injury and/or damage to the ballast and void the warranty. These instructions do not purport to cover all details or variations in equipment, nor to provide for every possible contingency related to installation, operation, maintenance or mounting situation. Should specific problems occur that are not addressed by these instructions, contact your sales representative or distributor for assistance. Retain these instructions for future use.



INSTRUCTIONS PERTAINING TO A RISK OF FIRE OR INJURY TO PERSONS - IMPORTANT SAFETY INSTRUCTIONS. Lighted lamp is HOT! WARNING - To reduce the risk of FIRE OR INJURY TO PERSONS: Turn off/unplug and allow to cool before replacing lamp. Lamp gets HOT quickly! Contact only switch/plug when turning on. Do not touch hot lens, guard, or enclosure (see diagram/picture). Keep lamp away from materials that may burn. Do not touch the lamp at any time. Use a soft cloth. Oil from skin may damage lamp. Do not operate the luminaire fitting with a missing or damaged shield. SAVE THESE INSTRUCTIONS. Xenon lamps do not require additional shielding.