

No-Load Electronic Transformer

TA100WD24LEDB15-0000



| | |
|--------------|----------------|
| Efficiency | > 85% |
| Power Factor | > 98% |
| Case TC | 90°C Max. |
| Protection | Input / Output |
| Storage | -30°C / +90°C |
| Humidity | 95% RH Max. |
| IP Rating | IP 65 |



FEATURES

- No load technology, works with both halogen & LED AC loads.**
- Isolated output power per NEC and UL safety requirements.
- UL recognized / listed power supply, meets UL2108 requirements.
- FCC Part 15 Class B compliant.
- Soft start, auto-reset, short circuit, overload and thermal protection.
- Dimmable with ELV type dimmers.
- Optional 0-10V dimming.
- Low profile, small compact design to fit in most enclosures.

ELECTRICAL SPECIFICATIONS

| Model Number | Wattage | Input Voltage | Output Voltage | Load Type | Form Factor | Dimming |
|----------------------|---------|------------------------|----------------|---|-------------|---------|
| TA100WD24LEDB15-0000 | 100W | 120V AC, 0.83A 50/60Hz | 24V DC | LED Strips, LED Bulbs, Incandescent & Halogen Bulbs | E7 | ELV |

MECHANICAL SPECS

| Available Form Factors | Dimensions |
|------------------------|-----------------|
| “E7” | 120 x 57 x 33mm |

E7

