

**TA10WA24LEDPL1**  
10W Dimmable Plug In



Efficiency	>85%
Power Factor	>95%
Case TC	90°C Max.
Protection	Input / Output
Storage	-30°C / +90°C
Class	Class 2 Power Supply
Dimming	ELV Dimmable
Dimming Option	Integrated Dimmer



**RoHS**



**FEATURES**

- Integrated dimming option available with on/off switch
- No load technology, works with both Halogen & LED AC loads
- Isolated output power per NEC and UL safety requirements
- UL listed, UL 8750, 1310
- Auto-reset; short circuit, overload and thermal protection
- Dimmable with ELV dimmers
- Flicker free dimming and excellent dimming range
- 3' 18/2 SPT-1 attached power cord with 1/4' stripped lead wires
- Class 2 power supply
- Efficient, high power factor, low THD
- For dry location use only

**MODEL SPECIFICATIONS**

120V					
Model Number	Input Voltage	Input Current	Output	Weight*	Available Form Factor
TA10WA24LEDPL1**	120V AC 50/60Hz	0.08A	10W 24VAC	208.5g	PL1
TA10WA24LEDPL1DM**	120V AC 50/60Hz	0.08A	10W 24VAC	208.5g	PL1 (integrated dim)

\* Weight based upon weight of PL1 model plug in without integrated dimmer.

\*\* B = Black, W = White

### MECHANICAL SPECS

FORM FACTOR	DIMENSIONS
PL1	90 x 49 x 33mm

