

TA60WA12LEDPL1
60W Dimmable Plug In



| | |
|----------------|----------------------|
| Efficiency | >85% |
| Power Factor | >95% |
| Case TC | 90°C Max. |
| Protection | Input / Output |
| Storage | -30°C / +90°C |
| Class | Class 2 Power Supply |
| Dimming | ELV Dimmable |
| Dimming Option | Integrated Dimmer |



FEATURES

- Integrated dimming option available with on/off switch
- No load technology, works with both Halogen & LED AC loads
- Isolated output power per NEC and UL safety requirements
- UL listed, UL 8750, 1310
- Auto-reset; short circuit, overload and thermal protection
- Dimmable with ELV dimmers
- Flicker free dimming and excellent dimming range
- 3' 18/2 SPT-1 attached power cord with 1/4' stripped lead wires
- Class 2 power supply
- Efficient, high power factor, low THD
- For dry location use only

MODEL SPECIFICATIONS

| 120V | | | | | |
|--------------------|-----------------|---------------|-----------|---------|-----------------------|
| Model Number | Input Voltage | Input Current | Output | Weight* | Available Form Factor |
| TA60WA12LEDPL1** | 120V AC 50/60Hz | 0.5A | 60W 12VAC | 208.5g | PL1 |
| TA60WA12LEDPL1DM** | 120V AC 50/60Hz | 0.5A | 60W 12VAC | 208.5g | PL1 (integrated dim) |

* Weight based upon weight of PL1 model plug in without integrated dimmer.
** B = Black, W = White

MECHANICAL SPECS

| FORM FACTOR | DIMENSIONS |
|-------------|----------------|
| PL1 | 90 x 49 x 33mm |

