

4CANRNDQJ60xx Series

60W Low Voltage Quick Connect Canopy



Efficiency	>85%
Power Factor	98%
Case TC	90°C Max.
Protection	Input / Output
Storage	-30°C / +90°C
Humidity	95% RH Max.
Class	Class 2 Power Supply
Dimming	ELV Dimmable



RoHS



FEATURES

- Compatible with most of the premier low voltage Quick Jack and Free Jack connectors/fixtures in the United States market
- Dimmable with ELV type dimmers
- Low profile design with no visible mounting screws
- Available in multiple finishes
- Transformer options for both halogen and LED loads

MODEL SPECIFICATIONS

60W					
Model Number	Input	Wattage	Output Voltage	Finish	Load Type
4CANRNDQJ60LEDSN	120V AC, 0.5A 50/60Hz	60W	11.8V AC/DC	Satin Nickel	Halogen & AC LED Bulbs
4CANRNDQJ60LEDBZ				Bronze	
4CANRNDQJ60LEDPN				Polished Nickel	
4CANRNDQJ60LEDWH				White	
4CANRNDQJ60LEDSB				Satin Brass	
4CANRNDQJ60LEDAB		60W	11.8V AC/DC	Aged Brass	
4CANRNDQJ60LEDGP				Gun Powder	
4CANRNDQJ60LEDBB				Brown Bronze	
4CANRNDQJ60LEDCH				Chrome	
4CANRNDQJ60LEDDC				Custom	

* Also available in constant current configurations

MECHANICAL SPECS

