

QLUXR5010W35LEDAMB
10W Round LED Board



Wattage	10W
Color	Amber
Available CCT	3000K
Lumen	1360lm
Efficacy	132lm/W
Number of LEDs	35
Beam Angle	120°
Dimensions	50mm OD
Dimming	Constant Current Reduction



FEATURES

- High efficacy lumen output 132 lm/W
- LM-80 compliant LEDs
- Tight Binning 3 Step Mac Adam Ellipses
- Uniform & crisp light source intensity
- Hot Spot Free Design
- Exceed ENERGY STAR lumen maintenance requirements
- Extra thin low profile
- Low heat generation, easy thermal management
- Easy to fit in new design or retrofit applications

APPLICATIONS

Ideal for new and retrofit architectural designs and lighting fixtures.

Indoor Lighting

- Recessed Can Light
- Ceiling Light
- Wall Sconces
- Table Lamps
- Fixtures
- Signage

Outdoor Lighting

- Street Lighting
- Marker Light
- Wall Sconces
- Signage Light

MODEL SPECIFICATIONS

Model Number	CCT	Typ. Wattage	Typ. Forward Voltage	Min. Forward Voltage	Max. Forward Voltage	Typ. Forward Voltage	Max. Forward Current
QLUXR5010W35LEDAMB	3000K	10W	21V	17V	21.7V	500mA	700mA

MECHANICAL SPECS

DIMENSIONS
50mm OD

